

Production Program Overview

(產品型錄)



Copper / Alloy * (銅 / 合金)	Thickness (厚度)	Width *** (寬度)
Copper (高純度紅銅) Cu-ETP / E-Cu58 Cu-HCP / SE-Cu58 Cu-OF / OF-Cu CuZn0.5 C 155	0.006 mm - 0.500 mm 0.006 mm - 0.500 mm 0.006 mm - 0.500 mm 0.006 mm - 0.500 mm 0.006 mm - 0.100 mm	1 mm - 650 mm ** 1 mm - 650 mm ** 1 mm - 650 mm ** 1 mm - 650 mm ** 1 mm - 300 mm **
Brass / Tombak (黃銅 / 仿金箔) CuZn10 CuZn12 CuZn15 CuZn30 CuZn37	0.006 mm - 0.100 mm 0.006 mm - 0.100 mm 0.006 mm - 0.100 mm 0.006 mm - 0.100 mm 0.006 mm - 0.100 mm	1 mm - 650 mm ** 1 mm - 650 mm ** 1 mm - 650 mm ** 1 mm - 650 mm ** 1 mm - 650 mm **
Bronze (磷銅) CuSn6	0.020 mm - 0.100 mm	1 mm - 320 mm **
Resistance alloys (阻抗性銅合金) CuNi6 CuNi8 CuNi44	0.006 mm - 0.150 mm 0.006 mm - 0.150 mm 0.006 mm - 0.150 mm	1 mm - 320 mm ** 1 mm - 320 mm ** 1 mm - 625 mm **
Nickel (純鎳) Nickel 99.6	0.006 mm - 0.100 mm	1 mm - 625 mm **
Silver (純銀) Silver 99.97% Silver 99.99% Silver 925 (Sterling - 標準純銀)	0.006 mm - 0.100 mm	1 mm - 320 mm **
Nickel-Silver (洋白板 / 德國銀) (German Silver / Neusilber) CuNi18Zn20	0.020 mm - 0.100 mm	1 mm - 570 mm **
Special materials (特殊合金) CIC - composite foil (銅-殷鋼-銅 複合式材料) (Invar Cu-cladded on both sides, plain or with Cu/Zn-treatment) - 或 銅/鋅 特殊處理	0.035 mm - 0.300 mm standard: 0.150 mm (標準厚度 : 0.150 mm)	1 mm - 610 mm **
Upgradings (表面特殊處理) Surface plated foils (表面附著其他合金) Strip finishing (表面特殊沉積處理)	tin-cladding (壓合錫箔) alu-cladding (壓合鋁箔) hot-dip tinning (熱浸錫) silvering (電鍍銀箔) nickel-cladding (壓合鎳箔) Cu-Treatment acc. to IPC-4562 (表面特殊銅粗化處理)	on one or both sides (單 / 雙面) on one or both sides (單 / 雙面) on one or both sides (單 / 雙面) on one or both sides (單 / 雙面)

* other copper qualities or alloys on request (其他種類之銅合金也可以探討、提供)

** depending on thickness (寬度之彈性亦與厚度有關)

*** most dimensions are also available as sheet, cut to length (我方亦可提供片材, 或切成段之帶狀材料)

Certified Quality Management system acc. to DIN EN ISO 9001 : 2000
(品質保證管理系統, 是根據 歐盟 DIN EN ISO 9001 : 2000 規定施行)

Member of IPC and EIPC
(本公司為國際 IPC and EIPC 正式會員)

Schlenk Metallfolien GmbH & Co. KG
Barnsdorfer Hauptstrasse 5
D-91 154 Roth
Germany

Tel.: +49 - (0)9171 - 808-0
Fax.: +49 - (0)9171 - 808 200
E-mail: foils@schlenk.de
Internet: http://www.schlenk.de